

Block Deployment Trailer

TRAILER SPECIFICATIONS 16' Trailer (DOT Compliant)

- Universal Mounting, Non-Skid Hot Dipped Galvanized Steel Grating Deck
- Hot-Dipped Galvanized
- Traversing Axle Carriage (To Balance load Distribution)
- Electric Brakes, (Both Axles) With Emergency Break-Away
- Storage/Tool Box
- Flip-Up Side Boarding Ladder

- 28,000-lb. GVWR
- 25,000-lb. Tongue Jack
- 7,000-lb. Leveling Jacks, Set of (4)
- 35,000-lb. Pintle Hitch with 7,000-lb. Tongue Load (Vertically Adjustable)
- Conspicuity Markings Around Perimeter of Trailer Deck
- Spare Tire

CONFIGURATION SPECIFICATIONS

- Powder Coated Steel Overhead Mounting Frame
- Galvanized Steel Sliding Beam for Lifting Blocks
- Beam Extends Beyond Rear of Trailer for Placing Blocks
- Honda EG4000CL Gasoline Generator to Power Trolley & Hoist
- Electric Sliding Trolley For Moving Blocks
- 6,000-lb Capacity Electric Chain Hoist for Lifting Concrete Blocks
- (4) 4,700-lb. 60" x 30" x 30" Concrete "LEGO" Blocks with Steel Reinforced Lifting Ring For Guy Line Attachment



3802 E. Broadway Rd. Phoenix, AZ 85040 Tel (602) 275-0662 Toll Free (800) 635-3658 WWW

NAME: Deployment Block Trailer DWG: SW-6570 CWS 1/22/2025



** PROPRIETARY AND CONFIDENTIAL ** Copyright © 2025 & Present Sun West Engineering, Inc. THIS PROPOSAL CONTAINS TRADE SECRETS AND OTHER PROPRIETARY AND CONFIDENTIAL INFORMATION OF SUN WEST ENGINEERING, INC.

THIS DOCUMENT AND IT'S CONTENTS, INCLUDING WITHOUT LIMITATION THE DRAWING AND OTHER INFORMATION HEREIN, ARE THE SOLE AND EXCLUSIVE PROPERTY OF SUN WEST ENGINEERING, INC.

ANY DUPLICATION, DISCLOSURE OR USE OF ANY PORTION OF THIS DOCUMENT REQUIRES THE PRIOR WRITTEN CONSENT OF SUN WEST ENGINEERING, INC.







